

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**

**This Page Blank (uspto)**



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification 4 :</b>  <b>G02B 27/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 85/ 04961</b>  <b>(43) International Publication Date:</b> 7 November 1985 (07.11.85)
<b>(21) International Application Number:</b> PCT/US85/00616 <b>(22) International Filing Date:</b> 8 April 1985 (08.04.85)  <b>(31) Priority Application Number:</b> 600,636 <b>(32) Priority Date:</b> 16 April 1984 (16.04.84) <b>(33) Priority Country:</b> US  <b>(71) Applicant:</b> HUGHES AIRCRAFT COMPANY [US/US]; 200 North Sepulveda Boulevard, El Segundo, CA 90245 (US).  <b>(72) Inventors:</b> MOSS, Gaylord, E. ; 13914 Bora Bora Way, Marina Del Rey, CA 90291 (US). COHN, Brian, D. ; 440 Bungalow Drive, El Segundo, CA 90245 (US). CHERN, Mao-Jin, J. ; 28414 Seamount Drive, Rancho Palos Verdes, CA (US). COOK, Lacy, G. ; 12444 Oxford Avenue, Hawthorne, CA 90250 (US). FERRER, John, J. ; 9100 Rayford Drive, Los Angeles, CA 90045 (US).		<b>(74) Agents:</b> ALKOV, Leonard, A. et al.; Hughes Aircraft Company, Post Office Box 1042, Bldg. C2, M.S. A126, El Segundo, CA 90245 (US).  <b>(81) Designated States:</b> DE (European patent), FR (European patent), GB (European patent), IT (European patent), JP, NL (European patent), SE (European patent).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** BIOCLULAR HOLOGRAPHIC HELMET MOUNTED DISPLAY**(57) Abstract**

A helmet mounted display uses a see-through visor (15) holographic combiner to provide, in the normal field of view of a helicopter pilot, a pair of images derived from an image source such as a miniature cathode ray tube (10). A source of the video display may be an infrared sensor mounted on an external turret underneath the helicopter. The turret rotates in response to helmet movements so that the pilot is continually provided with a dual image from the CRT display (10) which corresponds with the external scene as visible through the visor (15).

***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GA	Gabon	MR	Mauritania
AU	Australia	GB	United Kingdom	MW	Malawi
BB	Barbados	HU	Hungary	NL	Netherlands
BE	Belgium	IT	Italy	NO	Norway
BG	Bulgaria	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	LI	Liechtenstein	SN	Senegal
CH	Switzerland	LK	Sri Lanka	SU	Soviet Union
CM	Cameroon	LU	Luxembourg	TD	Chad
DE	Germany, Federal Republic of	MC	Monaco	TG	Togo
DK	Denmark	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali		
FR	France				

**BIOCULAR HOLOGRAPHIC HELMET MOUNTED DISPLAY****Background of the Invention****1. Field of the Invention.**

This invention relates to systems for enhancing the capability of a pilot to successfully operate an aircraft such as an attack helicopter in a low light level environment and, more particularly, to systems providing helmet mounted displays which combine infrared or other image detection and instrumentation symbology in a biocular helmet mounted display.

**2. Description of the Prior Art.**

Various systems are known in the prior art which have been developed to display symbology information or reticle information to an eyepiece for viewing by a pilot. Images from sensors such as radar, forward looking infrared (FLIR), low-light-level television imagery, electrophotical sensors and the like are combined with such information and presented to the pilot eyepiece. A number of such systems are described in an article entitled "Helmet-Mounted Display Interest Revives", Aviation Week & Space Technology, February 24, 1969. Some of these systems rely on binocular type arrangements with image intensifiers for amplifying the light level in the scene viewed by the pilot. Such systems suffer from the disadvantage that the field of view presented to both eyes

may not be the same, the image intensifier arrangement is cumbersome and heavy, and the eyepiece(s) constitute an object in front of the pilot's face which is likely to cause injury in the event of impact.

5           Other systems described in the article incorporate one or a pair of cathode ray tubes which generate images projected through optics for viewing by the pilot. The cathode ray tubes are mounted along the sides of the helmets and may provide the pilot with only a monocular  
10 view. In some of these versions, the pilot is required to view the display with one eye through an eyepiece equipped with a rubber cup to shut out ambient light. Variations in light intensity in the scenes presented to the pilot's eyes tend to produce eyestrain and the rubber cup becomes  
15 uncomfortable, possibly inducing headaches, in extended use. Furthermore, the viewing of separate images by the two eyes requires substantial training for a pilot to adapt to such an image presentation and tends to be tiring and confusing. Potential confusion or rivalry between  
20 displayed information and external background is to be avoided, if possible. The use of partially reflecting mirrors to display the images in front of the pilot's eyes undesirably cuts down on the available light for the outside scene which the pilot views directly. Also the  
25 distribution of components of a helmet mounted display is an important consideration, since the moments of inertia with respect to the wearer's spine should be minimized in order to avoid wearer discomfort and fatigue.

          A system called "Nighthelm" of Marconi Avionics  
30 Limited has been developed for use in modern attack helicopters which employ a steerable FLIR sensor to provide night flying imagery together with target sensing capability. The pilot can view the aircraft instruments and the real world through a pair of eyepieces on which  
35 are also projected images developed from a pair of image intensifiers situated along the helmet above the eyepiece.

By switching to another mode, the pilot may view on one eyepiece an image derived from a cathode ray tube (CRT) which displays FLIR imagery from the remote steerable sensor system. This system does not present images from the CRT to both eyes and thus, in the CRT viewing mode, presents different images to the pilot's eyes. Furthermore, the eyepieces are of heavy thick plastic, and they and the binocular/image intensifier portion of the system present a risk of injury to the pilot upon impact. A further disadvantage of a binocular system is the requirement that the binoculars be adjustable to accommodate the interpupillary dimensions for various users. Thus this system is also subject to many of the problems and disadvantages discussed above.

Patent 3,940,204 of Withrington discloses the use of holograms in head-up and in helmet mounted displays. The holographic lens of those displays is particularly constructed to correct particular optical aberrations and further compensation is afforded by the use of a relay lens having cylindrical surfaces. The image presented at the visor is monocular.

#### Summary of the Invention

In brief, particular arrangements in accordance with the present invention incorporate an improved type of helmet mounted display which allows the wearer to look through a clear visor and see a virtual image at infinity of a display generated on an object source such as a miniature cathode ray tube (CRT). The invention combines a number of optical elements with the helmet visor as an image display means to achieve a superior display system. The light display which is to be imaged to the viewer is developed by an object source, which may be for example a CRT, a liquid crystal display, fiber optics or the like. In one particular application of the invention, this object source develops a display which combines the signals from the FLIR sensor mounted in a turret beneath

the helicopter with symbology derived from the helicopter instrumentation. The FLIR turret is steerable through a head-tracking control system tied to the helmet.

5       Next to the object source is an image folding device which may be a prism or a mirror. This is provided for packing purposes, enabling the system to be more compact, and also serves to provide aberration correction.

10       Following the image folder in the optical path is a relay lens which is used to image the source onto the eyepiece focal surface. This relay lens is preferably a Cooke triplet or a modified triplet. It may incorporate aspheric surfaces on some of the lens elements, but such is not essential. It may be tilted and decentered if desired to accommodate the intended light path and to  
15       correct aberrations. The aperture stop may be above, below or within the lens.

      Adjacent the exit side of the relay lens is a beam splitting element which serves to divide the light beam out of the relay lens into two beams so that biocular  
20       images will be projected for each eye. Preferably in the present invention, the splitting element may be an X-cube prism, but it may also comprise a roof prism or known mirror beam splitters. The X-cube prism is a known element having internal reflective/transmissive surfaces  
25       which reflect two light beams laterally in opposite directions from a single incident light beam.

      Beam folders in the form of wing mirrors (which may have optical power, if desired) are laterally displaced from the splitting element in order to reflect  
30       the transverse beams out of the splitter toward the visor eyepieces.

      The eyepieces which form the respective biocular images are preferably in the form of embedded holograms laminated to the surface of a molded integral visor. As  
35       an alternative, partially silvered mirrors or CVD gratings might be employed, but the holographic elements are

preferred. These serve to collimate the light in order to present a virtual image (for the viewer) at infinity. The two biocular images present a total field-of-view overlap so that both eyes view the same image. In addition, by virtue of the transparent nature of the holographic elements, the visor serves as a combiner whereby the pilot sees not only the displayed images from the object source but also the outside scene in the direction in which he is looking. Because of the one piece, integrated nature of the visor, it is capable of serving in conventional fashion as a protective visor for the helmet wearer, in addition to its function as the display element in the overall display system.

In preferred arrangements in accordance with the invention, the biocular display system includes a particular three-element relay lens configuration employing aspheric surfaces and a cube beam splitter to generate a pair of real images of the miniature head-mounted CRT display. A folding prism is located in the optical path adjacent to the CRT to achieve a suitable positioning of the CRT in the system configuration which minimizes the moment of inertia of the respective display components. This enables the CRT to be mounted close to the helmet and following the profile of the user's head. The visor is an integrated part of the display and provides protection to the user's eyes. It accommodates most of the population of potential users without need for lateral adjustment and offers no visual obscuration to the wearer. The visor is also spaced from the user's face sufficiently to accommodate a pair of glasses worn by the user.

Two reflective holographic elements serving as eyepieces are located on the protective visor and transform the real CRT images from the beam splitter into a pair of identical virtual images at infinite distance which are then viewed by both eyes. Because the holograms

are almost transparent, the displayed imagery appears superimposed on the outside scene. The helmet visor display of the present invention provides a field of view which is  $30^\circ$  in elevation by  $40^\circ$  in azimuth with full overlap between the two image fields displayed on the visor. The visor holographic elements form combiners which introduce a bend angle in the rays from the CRT so that the optical path runs parallel to the forehead and as close to the head as is feasible, considering the space needed for padding inside the helmet.

In one particular embodiment, this configuration results in a  $58^\circ$  bend angle at the visor and a depression of the vertical field by  $5^\circ$  relative to the user horizontal. This depression is acceptable for attack helicopter use, since in field operation most targets are below the helicopter. After the CRT light is divided in the cube beam splitter, the resulting two beams are reflected by laterally disposed wing mirrors and then directed to the visor holographic elements. The display field of view is closely matched to the normal horizontal field of view. The optical system develops an exit pupil which is 15 mm. wide by 10 mm. high, located 90 mm. from the combiner. The centers of the left and right exit pupils are 62.5 mm. apart. The exit pupil size is large enough to accommodate the interpupillary separations of 90% of the population; that is, the separations of the fifth through the ninety-fifth percentiles of the population. Thus the need for providing adjustability of the viewing elements is eliminated and the goal of an integrated molded visor affording maximum protection of the wearer against the effects of object impact is achieved.

The selection and arrangement of optical elements of the system serve to compensate for inherent aberrations in certain components. Specifically, the tilt of the relay lens assembly and the wedge in the folding prism

correct for the axial coma which is introduced by the off axis holographic eyepiece elements. It is desirable that all elements of the relay lens have a common axis in order to minimize the alignment complexity of the relay lens.

5           In one preferred embodiment of the invention, the relay lens is essentially a variant of a Cooke triplet with aspheric surfaces. In a production environment, wherein the lens elements are formed of injection molded plastic, the aspheric surfaces are readily fabricated and  
10       this allows the relay lens (such as a Cooke triplet) to have fewer elements than comparable prior art systems. The relay lens may incorporate a spectral filter where needed in order to eliminate spurious blue and red images developing from spikes in certain CRT phosphors.

15           The preferred embodiment utilizes a 3/4-inch CRT display utilizing a P-43 phosphor having a spectral peak at 543 nanometers, the same wavelength to which the holograms are tuned. The folding prism is constructed so that the CRT centerline points to the left and slightly  
20       forward while lying in a plane that is largely horizontal. This configuration was chosen in order to simplify the design for the housing of the CRT. The relay lens, following the folding prism, comprises three elements (plus the spectral filter) all having a common axis.  
25       Where a filter is not necessary, it may be replaced by a clear piece of glass.

          The relay lens is followed by an X-cube prism, which is a set of four right-angled prisms joined in a cube to split the light which forms  
30       two images from the incident CRT source. These are then reflected by associated laterally-disposed wing mirrors to direct the images to the holographic elements in the visor. These in turn reflect the images through the bend angle at the visor, collimate the beams and direct the  
35       images to the pilot's eyes with the specified exit pupil.

          Thus, helmet mounted display systems in accordance

with the present invention present substantial improvements over helmet mounted displays which are known in the prior art. The hologram elements on the visor are virtually transparent and present no visual obscuration of the field of view. There is true biocular display of the images to both eyes from a single light source, with complete overlap of the two images. Rather than being a potential hazard to the wearer in the event of impact, as with the binocular or FLIR systems which mount heavy lenses, framework, etc., in front of the eyes, the integrated visor of the present system which is molded in one piece of tough lightweight plastic can withstand substantial impact forces and provides eye protection. The display system is extremely compact and lightweight, and the heavier components of the system are mounted symmetrically close to the wearer's head, thereby minimizing both the weight and the inertial moment of the overall display which is added to the helmet.

The holograms utilized in the present invention are developed in thin gelatin layers which are laminated on the integrated molded visor. The holograms are virtually transparent, thus developing a high see-through capability, and also provide a high reflection efficiency for the CRT images by virtue of the coordination of their wavelength characteristics to the particular properties of the CRT phosphor.

#### Brief Description of the Drawing

A better understanding of the present invention may be had from a consideration of the following detailed description, taken in conjunction with the accompanying drawing in which:

Fig. 1 is a block diagram illustrating the various elements of the display system of the present invention and the light paths therein;

Fig. 2 is a schematic diagram of one particular arrangement of the present invention, showing the relation

of the helmet mounted display to the user's head;

Fig. 3 is a schematic diagram illustrating various details of the elements making up the arrangement of Fig. 2; and

Fig. 4 is an orthogonal view of the arrangement of Fig. 3, showing the biocular use of the display.

Description of the Preferred Embodiment

The general arrangement of the present invention is illustrated schematically in the block diagram of Fig. 1. In this figure, light is shown emanating from an object source 10, which may be a CRT, and directed by an image folder 11 via a relay lens 12 to a splitting element 13. (The beam path from the source to the image folder is shown unfolded in the drawings for convenience of illustration.) The incident light is then split into two beams by the splitting element 13 which directs the beams laterally to a pair of folding members, shown in the form of wing mirrors 14 which redirect the two beams toward respective eyepieces, shown as the holographic elements of the visor 15, which collimate the light, redirect the beams toward the user's eyes, and form the exit pupil indicated. Each eye views the image at the corresponding exit pupil as a virtual image at infinity. The intermediate images, represented by the broken lines 16, are developed between the relay lens 12 and the visor 15.

The preferred embodiment is represented schematically in further detail in Figs. 2-4. The arrangement of the principal elements of the biocular system of the invention is shown in Fig. 2 in relation to the wearer's head (the helmet has been omitted for simplicity). The biocular display system is shown comprising a miniature cathode ray tube having a flat plate display element 17 bearing a phosphor on its inner surface 19. A fiber optic face plate, flat or curved as desired, might be used instead. As indicated in Fig. 3, the normal to the CRT plate 17 is aligned at  $30.274^\circ$  to

the reference line 21 of the system.

Next to the CRT plate 17 is a folding prism 18. The entrance face 20 of the prism 18 is orthogonal to the reference line 21 (and thus at  $30.274^\circ$  to the plane of the CRT plate 17) while the exit face 22 is at a wedge angle of  $8.36^\circ$ . The light from the cathode ray tube is internally reflected within the prism 18 which is spaced so that the entrance face 20 is located at a point 0.349 inch from a zero reference line 23, which is orthogonal to the reference line 21 at the outer surface of the CRT face plate 17.

Next to the folding prism 18 is the relay lens 30 comprising three lenses 32, 34 and 36 in a modified Cooke triplet, together with a spectral filter 38. The two outer lenses 32 and 36 of the triplet have aspheric surfaces while the intermediate lens 34 is a meniscus lens with spherical surfaces. The mounting of the relay lens off-axis serves to bend the axial ray 24 into coincidence with the reference line 21. The light transmitted by the relay lens 30 is then directed to an X-cube prism 40, better shown in Fig. 4, where it is split into a pair of laterally directed images which are reflected by wing mirrors 42 on opposite sides of the X-cube prism 40 and sent to the visor/eyepiece/combiner 44. Rays from a particular field point are collimated by the combiner 44 and an exit pupil is formed at 46 (represented by the broken lines 46 in Fig. 4).

The view in Fig. 4 is taken from the upper right of Fig. 2, parallel to the reference line 21 and the aligned faces of the folding prism 18 and X-cube prism 40. For simplicity, the wing mirrors 42 are not shown in the views of Figs. 2 and 3.

As indicated in Fig. 3, the aspheric lens 32 is mounted such that the point at which its upper surface 33 is intersected by the axial ray 24 is located 1.636 inches from the zero reference line 23. The upper face of the

X-cube prism 40 is 2.716 inches from the zero reference line 23, while the point at which the reflected axial ray 24 exits the combiner 44 is positioned 7.248 inches from the zero reference line 23. The combiner 44 is oriented  
5 such that its element axis in the plane of Fig. 3 forms an angle of  $30.24^\circ$  with the path of the axial ray exiting the combiner 44 (extending in the direction of the exit pupil 46).

The location of the wing mirrors 42 relative to  
10 the combiner 44 is limited by a requirement for a  $35^\circ$  see-through look-up capability and necessary head clearance (see Fig. 2). This in turn fixes the location of the X-cube prism 40. First order and packaging considerations (especially the need for a long back focus  
15 to allow the inclusion of the fold prism 22) dictate that the aperture stop (of which the exit pupil 46 is an image) fall slightly above the X-cube prism 40. This is also one of the positions of the aperture stop for which the relay lens 30 can most readily be designed for superior  
20 performance. However, with minor modification of the design, the stop may be located above or within the relay lens 30, if desired. Sufficient eye relief has been incorporated into the display system to allow the user to wear glasses and a standard oxygen mask. Given the eye  
25 relief and aperture stop location desired, the focal length of the combiner 44 and the magnification of the relay lens 30 are readily determinable. Because the user looks through the visor 44, see-through distortion is carefully controlled. Also, particular care has been  
30 taken in the design of the preferred embodiment to insure that there is minimal see-through variation when crossing the border of the combiner 44.

The axis of the relay lens 30 comprising the elements 32, 34, 36 and 38 (represented by the dot-dash  
35 line 39) is at an angle of  $5.29^\circ$  to the reference axis 21; and the point at which the axis 39 intersects the surface

33 of the lens 32 is displaced from the reference line 21 by 0.129 inch.

A summary of the optical characteristics of the particular embodiment of the present invention depicted in Figs. 2-4 is set forth in the following Table I:

TABLE I

	<u>Parameter</u>	<u>Value</u>
	<b>System</b>	
	Horizontal field of view	40°
10	Vertical field of view	30°
	Exit pupil width	15mm.
	Exit pupil height	10mm.
	Effective focal length	26.7mm.
	Horizontal f-number	1.77
15	Vertical f-number	2.70
	CRT diameter	19.0mm.
	Exit pupil separation	62.5mm.
	Wavelength	543.0nm.
	<b>Internal</b>	
20	Combiner focal length	50.8mm.
	Combiner f-number	3.4
	Combiner bend angle	58°
	Relay lens f-number	1.1
	Relay lens field of view	30°
25	Approximate relay lens width	26mm.

A layout similar to that shown in Fig. 3 is appropriate if a fiber face plate CRT is substituted for the glass face plate 17 which is shown. In such a case, however, the spacing and alignment of the elements 18, 32, 34, 36, 38 and 40 would be adjusted slightly to account for the fact that the image is developed at the outer face of the CRT instead of the inner surface 19 as indicated in Fig. 3.

It will be apparent to those skilled in the art that the various parameters set forth hereinabove with respect to the particular embodiment depicted in Figs. 2-4

are selected in accordance with acceptable design principles. Other parameters of the system, not specified, such as the prescriptions for the lens surfaces of the elements in the relay lens 30, may be chosen in accordance with such principles. These principles are well known to those skilled in the art and may be found in any good textbook on optical engineering. One such text is "Modern Optical Engineering" by Warren J. Smith (McGraw-Hill, Inc. 1966).

There has thus been shown and described hereinabove an improved type of helmet mounted display which allows the wearer to look through a clear visor and see a virtual image at infinity of a display generated on a miniature CRT. This is of particular utility where movement of the helmet is used to control the direction of a FLIR sensor turret from which the portion of the CRT image representing the external scene is derived. All of the elements making up the display system, with the sole exception of the combiner which constitutes the helmet visor, are mounted on the helmet out of the field of view and away from any position where they might cause injury to the user. The present display, particularly the helmet visor, is compatible with on board life support systems, such as the pilot's spectacles, oxygen mask, etc. The incorporation of the X-cube splitter in combination with the integrated visor achieves added protection against impact for the pilot with improved compactness, reduction in weight, and minimal moment of inertia of the helmet mounted display. As compared with known prior art systems, the biocular system of the present invention establishes a larger field of view, a larger exit pupil, improved resolution, a complete biocular scene overlap to each eye and a normal viewing field. Moreover, the display system develops easy adaptability of the user with a minimum of instruction and training being required. The result is an enhancement of the safety and effectiveness

of operation of helicopters or other aircraft in which such a system may be installed.

5        Although there have been described above specific arrangements of a biocular holographic helmet mounted display in accordance with the invention for the purpose of illustrating the manner in which the invention may be used to advantage, it will be appreciated that the invention is not limited thereto. Accordingly, any and all modifications, variations or equivalent arrangements  
10       which may occur to those skilled in the art should be considered to be within the scope of the invention as defined in the annexed claims.

CLAIMSWhat is Claimed is:

1           1. Biocular display apparatus for mounting on a helmet to provide biocular images combined with real world cues received through a helmet visor comprising:

5                 an object source device to be generally mounted adjacent the helmet for providing a display to be directed generally downwardly along the forward portion to the helmet;

10                 beam splitting means for splitting incident light from the object source device into a pair of oppositely directed transverse beams;

15                 a generally transparent visor for mounting on said helmet and having dual eyepieces oriented at a selected angle, said eyepieces being substantially transparent to permit the helmet wearer to view external scenes therethrough but having the capability of reflecting and collimating light directed thereto from the object source device to project biocular images at respective exit pupils in the general vicinity of the helmet wearer's eyes;

20                 means between the object source device and the splitting means for directing light from the object source device to the splitting means; and

25                 fold means adjacent the splitting means for directing the two light beams from the splitting means toward the respective eyepieces.

1           2. Apparatus of Claim 1 wherein the spacing  
between the visor eyepieces is fixed at a predetermined  
distance between them, and wherein the exit pupils are  
of such a size that the apparatus can be used by a  
5   substantial portion of the general population without  
mechanical adjustment.

1           3. Apparatus of Claim 2 wherein the eyepieces  
afford the helmet wearer a normal field of view without  
visual obscuration, and wherein the biocular images  
provide substantially full overlap with each other.

1           4. Apparatus of Claim 1 wherein the object source  
device is a cathode ray tube capable of providing a  
video display combining video signals derived from a  
real world cue sensor with selected instrumentation  
5   symbolology.

1           5. Apparatus of Claim 4 wherein the cathode ray  
tube is oriented in a generally horizontal plane.

1           6. Apparatus of Claim 1 wherein the means between  
the object source device and the splitting means comprise  
means for bending the light beam from the object source  
device display and projecting it toward the splitting  
5   means.

1           7. Apparatus of Claim 6 wherein the bending  
means comprise an image folding element and a relay  
lens mounted in succession along the light path between  
the object source device and the splitting means.

1           8. Apparatus of Claim 7 wherein the image folding  
means comprise a prism having an exit face oriented at  
a preselected wedge angle selected to provide aberration  
correction of the light beam.

1           9. Apparatus of Claim 7 wherein the relay lens  
comprises a triplet of individual lenses separately  
spaced from each other.

1           10. Apparatus of Claim 9 wherein the triplet of  
lenses comprises first and third lenses having aspheric  
surfaces and an intermediate meniscus lens having  
spherical surfaces.

1           11. Apparatus of Claim 10 wherein the relay lens  
further includes a filter for eliminating unwanted  
colors from the object source device display.

1           12. Apparatus of Claim 7 wherein the beam splitting  
means is generally centrally oriented relative to the  
axial ray of incident light projected from the relay  
lens.

1           13. Apparatus of Claim 1 wherein the beam splitting  
means comprise an X-cube prism having internal surfaces  
which are partially reflective and partially transmissive  
to develop the transverse beams from incident light at  
5 one external face of the prism.

1           14. Apparatus of Claim 13 wherein the fold means  
comprise a pair of wing mirrors mounted transversely  
on opposite sides of the X-cube prism and angled to  
reflect the transverse beams respectively in the direction  
5 of the visor eyepieces.

1        15. Apparatus of Claim 1 wherein the visor is a  
unitary molded plastic member having respective right  
and left viewing portions shaped to develop a focusing  
effect for light reflected from a partially reflective  
5 surface thereof.

1        16. Apparatus of Claim 15 wherein the visor is  
mounted at a selected angle relative to the axial ray  
of the light beams incident thereon to develop a fold  
angle for said light beams suitable for projecting the  
5 light beams toward the eyes of a wearer of the helmet.

1        17. Apparatus of Claim 16 wherein the visor  
eyepieces comprise thin surface elements laminated  
respectively to the right and left portions of the  
visor and having holograms embedded therein.

1        18. Apparatus of Claim 17 wherein the object  
source device is a cathode ray tube and wherein said  
holograms are fabricated to have a tuned wavelength  
matching the phosphor of the cathode ray tube.

1        19. A biocular holographic display device for  
mounting on a helmet to provide a transparent image  
display through which real world cues may be viewed  
comprising:

5                a miniature cathode ray tube having a face  
plate facing in a generally horizontal direction;  
                 a combiner in the form of a helmet visor  
bearing a pair of substantially clear holographic  
elements through which the user may view an external  
10 scene, said holographic elements constituting eyepieces  
which are displaced by a preselected distance on opposite  
sides of the midpoint of the visor; and

means comprising a plurality of optical elements positioned between the cathode ray tube face plate and the visor for bending the beam of light rays from the cathode ray tube face plate, splitting said beam into a pair of like beams, and directing said pair of beams to respective eyepieces on said visor for biocular image viewing by a user.

1        20. The device of Claim 19 wherein the biocular images provide substantially complete image overlap to to viewer.

1        21. The device of Claim 19 wherein the field of view provided through the visor eyepiece through which an external scene may be viewed is substantially without visual obscuration by any part of the device.

1        22. The device of Claim 19 wherein the visor is mounted at an angle in the vertical plane such that a bend angle in excess of 50° is developed in the axial ray of the projected image.

1        23. The device of Claim 19 wherein said optical elements means comprise a folding prism, a relay lens, an X-cube prism for splitting the beam from the cathode ray tube into a pair of laterally transmitted beams, and a pair of wing mirrors mounted on opposite sides of the X-cube prism for reflecting the split beams toward the combiner.

1        24. The device of Claim 23 wherein the optical elements are oriented such that the relay lens and the folding prism are displaced in a vertical plane from a reference line which is parallel to the axial rays of the split beams as they are projected on the combiner.

1        25. The device of Claim 19 wherein the cathode  
ray tube face plate is of glass with a phosphor on the  
inner surface thereof, and wherein the holographic  
elements are formed with a tuned wavelength selected to  
5 match the phosphor.

1        26. The device of Claim 24 wherein the relay lens  
comprises a triplet of lens elements including a pair  
of aspheric lenses arrayed on opposite sides of, and  
spatially separated from, a meniscus lens.


1        27. The device of Claim 26 wherein the relay lens  
further includes a spectral filter following said  
triplet.

1        28. The device of Claim 26 wherein the axis of  
the relay lens is angularly displaced from the reference  
line by a predetermined angle.

1        29. The device of Claim 19 wherein the exit pupil  
of each of the dual images reflected from the combiner  
at a plane 90mm. distant from the combiner as measured  
along the axial ray of the projected image is 15mm.  
5 wide and 10 mm. high.

1        30. The device of Claim 29 wherein the dimensions  
of the exit pupils and the distance between the eyepieces  
are selected to accommodate approximately 90% of the  
general population of users.

Fig. 1.



2 / 4




Fig. 2.




Fig. 3.




Fig. 4.

# INTERNATIONAL SEARCH REPORT

International Application No PCT/US 85/00616

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (if several classification symbols apply, indicate all) <sup>6</sup> According to International Patent Classification (IPC) or to both National Classification and IPC IPC <sup>4</sup> : G 02 B 27/00																							
<b>II. FIELDS SEARCHED</b> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; margin: 5px 0;">Minimum Documentation Searched <sup>7</sup></div> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 30%; text-align: left; border-bottom: 1px solid black;">Classification System</th> <th style="width: 70%; text-align: left; border-bottom: 1px solid black;">Classification Symbols</th> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;">IPC<sup>4</sup></td> <td style="padding: 5px;">G 02 B 27/00</td> </tr> </table> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; margin: 5px 0;">Documentation Searched other than Minimum Documentation to the extent that such Documents are Included in the Fields Searched <sup>8</sup></div>			Classification System	Classification Symbols	IPC <sup>4</sup>	G 02 B 27/00																	
Classification System	Classification Symbols																						
IPC <sup>4</sup>	G 02 B 27/00																						
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT <sup>9</sup></b> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%; text-align: left; border-bottom: 1px solid black;">Category <sup>10</sup></th> <th style="width: 70%; text-align: left; border-bottom: 1px solid black;">Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup></th> <th style="width: 20%; text-align: left; border-bottom: 1px solid black;">Relevant to Claim No. <sup>13</sup></th> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">X</td> <td style="border-right: 1px solid black; padding: 5px;">GB, A, 2006463 (HUGHES AIRCRAFT) 2 May 1979, see figures 4,7,16a,16b; page 1, lines 54-63; page 2, lines 51-56; page 3, lines 15-27, lines 49-51; page 7, lines 49-65</td> <td style="padding: 5px;">1,2,4,15,17, 19,30</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="border-right: 1px solid black; padding: 5px;">see page 4, lines 1-23</td> <td style="padding: 5px;">3,5-7,12,14, 16,23,24,28</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="border-right: 1px solid black; padding: 5px;">US, A, 3940204 (WITHRINGTON) 24 February 1976, see figures 1-3, 11-14; column 9, line 56 - column 10, line 8 (cited in the application)</td> <td style="padding: 5px;">4-8,22,24,28</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="border-right: 1px solid black; padding: 5px;">GB, A, 2100466 (G.E.C.) 22 December 1982, see page 1, lines 52-60; page 1, line 84- page 2, line 44; figure 3</td> <td style="padding: 5px;">7-9,26</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="border-right: 1px solid black; padding: 5px;">US, A, 4001499 (DOWELL) 4 January 1977, see figure 1</td> <td style="padding: 5px;">9,26</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="border-right: 1px solid black; padding: 5px;">GB, A, 1581926 (ELLIOT BROS. LTD.) 31 Decem- ber 1980, see page 2, lines 63-67; figure 2</td> <td style="padding: 5px;">9</td> </tr> </table>			Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>	X	GB, A, 2006463 (HUGHES AIRCRAFT) 2 May 1979, see figures 4,7,16a,16b; page 1, lines 54-63; page 2, lines 51-56; page 3, lines 15-27, lines 49-51; page 7, lines 49-65	1,2,4,15,17, 19,30	A	see page 4, lines 1-23	3,5-7,12,14, 16,23,24,28	A	US, A, 3940204 (WITHRINGTON) 24 February 1976, see figures 1-3, 11-14; column 9, line 56 - column 10, line 8 (cited in the application)	4-8,22,24,28	A	GB, A, 2100466 (G.E.C.) 22 December 1982, see page 1, lines 52-60; page 1, line 84- page 2, line 44; figure 3	7-9,26	A	US, A, 4001499 (DOWELL) 4 January 1977, see figure 1	9,26	A	GB, A, 1581926 (ELLIOT BROS. LTD.) 31 Decem- ber 1980, see page 2, lines 63-67; figure 2	9
Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>																					
X	GB, A, 2006463 (HUGHES AIRCRAFT) 2 May 1979, see figures 4,7,16a,16b; page 1, lines 54-63; page 2, lines 51-56; page 3, lines 15-27, lines 49-51; page 7, lines 49-65	1,2,4,15,17, 19,30																					
A	see page 4, lines 1-23	3,5-7,12,14, 16,23,24,28																					
A	US, A, 3940204 (WITHRINGTON) 24 February 1976, see figures 1-3, 11-14; column 9, line 56 - column 10, line 8 (cited in the application)	4-8,22,24,28																					
A	GB, A, 2100466 (G.E.C.) 22 December 1982, see page 1, lines 52-60; page 1, line 84- page 2, line 44; figure 3	7-9,26																					
A	US, A, 4001499 (DOWELL) 4 January 1977, see figure 1	9,26																					
A	GB, A, 1581926 (ELLIOT BROS. LTD.) 31 Decem- ber 1980, see page 2, lines 63-67; figure 2	9																					
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p><sup>10</sup> Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p> </div> </div>																							
<b>IV. CERTIFICATION</b> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;">           Date of the Actual Completion of the International Search            29th June 1985         </td> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;">           Date of Mailing of this International Search Report            02 AOUT 1985         </td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 5px;">           International Searching Authority            EUROPEAN PATENT OFFICE         </td> <td style="border-bottom: 1px solid black; padding: 5px;">           Signature of Authorized Officer             G.L.M. Kruidenberg         </td> </tr> </table>			Date of the Actual Completion of the International Search 29th June 1985	Date of Mailing of this International Search Report 02 AOUT 1985	International Searching Authority EUROPEAN PATENT OFFICE	Signature of Authorized Officer G.L.M. Kruidenberg																	
Date of the Actual Completion of the International Search 29th June 1985	Date of Mailing of this International Search Report 02 AOUT 1985																						
International Searching Authority EUROPEAN PATENT OFFICE	Signature of Authorized Officer G.L.M. Kruidenberg																						

## III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)

Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No
A	GB, A, 1602373 (SECRETARY OF STATE FOR DEFENCE) 11 November 1981, see page 1, lines 87-100 --	11,18,25,27
A	US, A, 4048653 (SPOONER) 13 September 1977, see whole document  -----	

# ANNEX TO THE INTERNATIONAL SEARCH REPORT ON

INTERNATIONAL APPLICATION NO.

PCT/US 85/00616 (SA 9389)

This Annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 23/07/85

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB-A- 2006463	02/05/79	NL-A- 7810398	19/04/79
		FR-A,B 2406216	11/05/79
		DE-A,B,C 2843661	19/04/79
		JP-A- 54070850	07/06/79
US-A- 3940204	24/02/76	FR-A,B 2298809	20/08/76
		GB-A- 1489323	19/10/77
		SE-A- 7600429	26/07/76
		SE-B- 414084	07/07/80
GB-A- 2100466	22/12/82	EP-A- 0066402	08/12/82
		US-A- 4468101	28/08/84
US-A- 4001499	04/01/77	FR-A,B 2265616	24/10/75
		DE-A- 2513343	16/10/75
		GB-A- 1503646	15/03/78
GB-A- 1581926	31/12/80	None	
GB-A- 1602373	11/11/81	None	
US-A- 4048653	13/09/77	GB-A- 1489758	26/10/77
		CA-A- 1048777	20/02/79
		JP-A- 51066036	08/06/76

**This Page Blank (uspto)**